

DS-K1102A Card Reader



- PC+ABS material shell with PMMA panel design and alloy decoration
- Equipped with the 32-bit high-speed processor
- Built-in audible beeper
- Display the reader status with LED indicator
- RS-485 and Wiegand (W26/ W34) protocol
- Tamper-proof alarm
- Online upgrade function (under the 485 communication mode). Card reader can degrade to pre-upgrade status in case of upgrading failed
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader
- Dust-proof and water-proof design
- Supports reading EM card (Frequency: 125 KHz) (DS-K1102AE/DS-K1102AEK/DS-1102AEM)
- Meets the standard of ISO 14443-A. Supports reading Mifare card (Frequency: 13.56 MHz). (DS-K1102AM/DS-K1102AMK/DS-K1102AEMK)



▪ Specification

System	
Processor	32 bit
Audio	
Audio alert	Beeper
Authentication	
Card reading frequency	DS-K1102AE/DS-K1102AEK/DS-K1102AEM/DS-K1102AEMK: 125 KHz DS-K1102AM/DS-K1102AMK/DS-K1102AEM/DS-K1102AEMK: 13.56 MHz
Card reading distance	≤ 50 mm (1.97")
Function	
ID settings	via DIP switch
Others	
Keypad	DS-K1102AE/DS-K1102AM/DS-K1102AEM: No Keypad DS-K1102AEK/DS-K1102AMK/DS-K1102AEMK: Keypad with 12 keys (0 to 9, *, #)
Indicator	Power indicator; Status LED indicator
Power supply	12 VDC, 500 mA, 2 W
Working temperature	-20°C to 65°C (-4°F to 149°F)
Working humidity	10% to 90% (Non condensing)
Dimensions	121 mm × 86.5 mm × 14 mm (4.76" × 3.41" × 0.55")
Protective level	IP64
Weight	≤ 0.14 kg
Installation	Applied for 86 & 120 gang box
Approval	FCC, CE

▪ Available Model

DS-K1102AE, DS-K1102AEK, DS-K1102AEM, ,DS-K1102AEMK, DS-K1102AM, DS-K1102AMK

Distributed by




Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com