

ZKB103

1D Laser Wireless Barcode Scanner



ZKB103 is a wireless industrial hand-held one-dimensional gun-type barcode scanner with good reading performance. It can easily read barcodes on different mediums such as paper, commodity, screen, etc.

The product adopts enhanced wireless 2.4G transmission technology. The outdoor environment's effective distance can reach more than 150 meters and support both wired and wireless transmission modes. It can be mainly used in mobile payment, barcode scanning, inventory checking, etc.

Features

- Ergonomic design, more convenient operation, more comfortable grip;
- Enhanced wireless 2.4G transmission technology, reliable outdoor open transmission distance up to 150 meters, while supporting wired transmission without switching;
- 16MB storage, support synchronous mode scan and transfer, support storage mode, and store more than 100,000 commodity codes in large capacity;
- Indicator and buzzer can clearly reflect the scanning results.

Specifications

General	
Weight	About 210g (without wire)
Dimensions (LxWxH)	175mm × 72mm × 100mm
Wire length	1.8m
Interface type	2.4G, Standard USB (Full Speed, USB 2.0)
Material	ABS+PC
Color	White
User indicators	LED, buzzer
Scanning Performance	
Light source	Visible laser diode, wavelength: 525nm
Processor	ARM -8bit
Startup time	4s
Analytical ability	≥3mil/0.076mm@PCS%90
Depth of focus	50-0cm
Scanning mode	Manual scanning, Constant light scanning
Reading angle	Roll: °30±; Pitch: °60± (or greater); Yaw: °50± (or greater)
Input power	85mA @ 5V DC
Scanning speed	250 times per second
Light levels	5000Lux
Decode capabilities	EAN/JAN8-, EAN/JAN13-, UPC-A, UPC-E, CODE 39, CODE 93, CODE128, Codabar, GS128-1, Interleaved 2 of 5, MSI, ISBN/ISSN, ISBT, etc.
Wireless Performance	
Wireless standard	2.4GHz (IMS)
Transmission distance	150m (Outdoor open environment)
Storage capacity	100000 commodity codes (16MB)
Battery capacity	1600mAh
Battery charging time	About 5 hours
Continuous working hours	≥20hours
Standby time	4 weeks
Environmental	
Operating temperature	°0C to °50C
Storage temperature	°30-C to °60C
Relative humidity	%5 to %95 (Non condensing state)
Protection level	IP54
Drop Test	1.8m
High and low temperature test	Work properly for 30 minutes under simulation of temperature of °30-C and °60C
Transport vibration test	10H@125RPM

